



Declaration of Performance

**UK
CA**

ER Certification 8511

CAW (Cornwall) Ltd
Threemilestone Industrial Estate, Truro, Cornwall, TR4 9LD

24

8511 – CPR – ABC 1039

DoP No: CAW012

Technal Commercial aluminium door, fitted with emergency exit panic hardware
Intended for use in domestic and commercial refurbishment or new building applications on escape routes.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

Watertightness: NPD

Dangerous substances: None released under normal indoor use.

Resistance to wind load: NPD

Impact resistance (glazed doors with injury risk only): NPD

Load-bearing capacity of safety devices: Not fitted

Height & width (clear opening): NPD

Ability to release (locked doors on escape routes only): Emergency exit panic hardware complies with EN1125 or EN179 when fitted (1)

Acoustic performance: NPD

Thermal transmittance: $\leq 3.9 \text{ W/m}^2\text{k}$ (2)

Radiation Properties: NPD

Air permeability: NPD

(1): Continuous surveillance of Factory Production Control (FPC) in compliance with AVCP System 1 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010 by ER Certification, Notified Test Body No. 8511

For all other essential characteristics, Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

(2) Thermal Transmittance calculation approved by Exova Warrington Fire, Notified Test Body No. 1104, Ref Report No.WIL328908.

CLIVE PASCOE
Name (Print)

Signed

C. R. Pascoe

MANAGING DIRECTOR
Position

05.01.2024 TRURO
Date and Place of Issue